



## DF1 Serial Port Expander Gateway

### 5102-DFS3-DFM

The ProLinx DF1 Serial Port Expander Gateway allows you to attach up to three separate DF1 master devices to a single DF1 slave.

The module is designed to act as a multiplexer, allowing simultaneous connections from multiple DF1 masters to a single DF1 slave. A common use for the module is to have an HMI panel, SCADA package, and Programming software all communicating to the same DF1 channel 0 port of the Rockwell Automation processor.

The module provides a single DF1 Master port and three DF1 Slave ports.

### DF1 Master/Slave

The DF1 Master/Slave Protocol driver provides extensive support for both Master and Slave implementations of the protocol. The serial port on the gateway is user-configurable to support the DF1 protocol (Master or Slave, Error Checking, Baud rate, etc).

#### General Parameters

Communication parameters	Local Station ID: 0 to 254 Ports 1 to 3 Baud Rate: 110 to 115K baud Stop Bits: 1 Data Size: 8 bits Parity: None, Even, Odd RTS Timing delays: 0 to 65535 ms
Error Checking	BCC and CRC
Miscellaneous	Full hardware handshaking control, providing radio, smart modem and Multi-drop support Floating point data supported

### DF1 Master Protocol Specifications

The ports on the module can be individually configured as Master ports. When configured in master mode, the DFCM module is capable of reading and writing data to remote DF1 devices.

#### DF1 Master Driver

DF1 Modes	Full-Duplex – Master (Module generates commands) Half-Duplex – Polling
Command List	Up to 100 commands per Master port, each fully-configurable for function, slave address, register to/from addressing and word/bit count

### DF1 Serial Port Expander Gateway 5102-DFS3-DFM

*The Serial Port Expander adds three additional slave ports for a DF1 based device. This allows users to connect programming software, HMI, and modems to processors simultaneously. Commands from the host devices are passed through the module and routed directly to the front port of the processor. This allows a processor's port to be expanded to allow communication with a variety of devices at the same time. Typical applications include local ladder configuration, local operator interface, and wireless concentrator for remote programming and data collection.*

### How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

#### Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com  
Languages spoken include: Chinese, Japanese, English

#### Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com  
Languages spoken include: French, English

#### North America

+1.661.716.5100, support@prosoft-technology.com  
Languages spoken include: English, Spanish

#### Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com  
Languages spoken include: Spanish, English

#### Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com  
Languages spoken include: Portuguese, English

### DF1 Master Driver

Polling of Command List	User-configurable polling of commands, including disabled, continuous, and on change of data (write only)
-------------------------	---

### DF1 Slave Protocol Specifications

The ports on the module can be individually configured to support the Slave mode of the DF1 protocol. When in slave mode, the module can accept DF1 commands from a master to read/write data stored in the module's internal registers.

### DF1 Slave Driver

DF1 Modes	Full Duplex – Slave (not peer mode) Half Duplex – Polled
Configurable parameters per slave port	Data Table File Start (File N[x] 0 to 999) Data Table File Size (1 to 1000 words) Data Table location in database (0 to 3999)

### General Specifications

The ProLinx Communication Modules provide connectivity for two or more dissimilar network types. The modules, encased in sturdy extruded aluminum, are stand-alone DIN-rail mounted protocol gateways, providing communication between many of the most widely used protocols in industrial automation today.

### Hardware Specifications

Specification	Description
Power Supply	24 VDC nominal 18 to 36 VDC allowed Positive, Negative, GND Terminals 2.5 mm screwdriver blade
Current Load	500 mA max@ 24 VDC
Operating Temperature	-20 to 50°C (-4 to 122°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Relative Humidity	5 to 95% (non-condensing)
Dimensions	Standard: 5.20H x 2.07W x 4.52D in. (13.2cmH x 5.25cmW x 11.48cmD) Extended: 5.20H x 2.73W x 4.52D in. (13.2cmH x 6.934cmW x 11.48cmD)
LED Indicators	Power and Module Status Application Status Serial Port Activity LED Serial Activity and Error LED Status
Configuration Serial Port	DB-9M RS-232 only No hardware handshaking
Ethernet Port (Ethernet modules only)	RJ45 Connector Link and Activity LED indicators

Specification	Description
Application Serial Ports	RS-232/422/485 RS-232 handshaking configurable RS-422/485 screw termination included
Serial Port Isolation	2500V RMS port signal isolation per UL 1577 3000V DC min. port to ground and port to logic power isolation
Shipped with Each Unit	Mini-DIN to DB-9M serial cables 4 ft RS-232 configuration cable 2.5mm screwdriver CD (docs and Configuration utility) RS-422/485 DB-9 to Screw Terminal Adaptor (1 or 4, depending on ports)

### ProSoft Configuration Builder

ProSoft Configuration Builder (PCB) provides a quick and easy way to manage module configuration files customized to meet your application needs. PCB is not only a powerful solution for new configuration files, but also allows you to import information from previously installed (known working) configurations to new projects.

### Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

### Ordering Information

To order this product, please use the following:

**5102-DFS3-DFM** DF1 Serial Port Expander Gateway

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

### Distributors:

Place your order by email or fax to:

**North American / Latin American / Asia Pacific**  
orders@prosoft-technology.com,  
fax to +1 661.716.5101

**Europe**  
europe@prosoft-technology.com,  
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.  
May 03, 2007