



# Modbus TCP/IP to DNP 3.0 Master Gateway

## 5201-MNET-DNPM

The ProLinx Modbus TCP/IP to DNP 3.0 Master Gateway creates a powerful connection between devices on a Modbus TCP/IP network and DNP slave devices. This stand-alone DIN-rail mounted protocol gateway provides one Ethernet port and one serial port.

The Modbus TCP/IP protocol driver can interface many different protocols into Schneider Electric Quantum processors as well other solutions supporting the protocol. The MNET driver supports Client and Server connections, and when coupled with the Web option provides a web/ftp interface as well.

The DNP 3.0 Master protocol driver supports Master implementations of the protocol on one port. This port is fully configurable.

## Modbus TCP/IP

The Modbus TCP/IP driver interfaces with a common internal database in the module. This permits the sharing of data between the Modbus TCP/IP and other networks and devices.

---

### Modbus TCP/IP Server

General	Server supports up to 5 independent connections each to Modbus TCP/IP clients on Service Port 502 using the standard MBAP protocol, and Service Port 2000.
---------	--

Configurable Parameters	Module IP Address Modbus address offsetting
-------------------------	--

---

### Modbus TCP/IP Client

General	Actively reads and writes data with Modbus TCP/IP compatible devices.  One client connection (up to 100 servers/devices with 100 commands)
---------	--

Configurable parameters	Number of active commands, Min Command Delay, Response Timeout, Retry Count, Command Error Pointer
-------------------------	--

Command List	Up to 100 fully configurable commands on the Client port
--------------	--

---

## Modbus TCP/IP to DNP 3.0 Master Gateway 5201-MNET-DNPM

*The MNET-DNPM modules are the ideal solution for the many applications where Modbus TCP/IP connectivity can be used to integrate DNP Master devices into a system. The Modbus TCP/IP gateway is a powerful module designed with both Client and Server support, enabling easy connection to other Modbus TCP/IP devices (Modicon processors and many others). In combination with the DNP 3.0 Master device support, the module provides a very powerful interface to the many DNP devices which are in use in the industrial marketplace today. Applications for the module are found in most industries, especially Manufacturing, Oil and Gas, Electrical Power and Food Processing.*

## How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

### Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com  
Languages spoken include: Chinese, Japanese, English

### Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com  
Languages spoken include: French, English

### North America

+1.661.716.5100, support@prosoft-technology.com  
Languages spoken include: English, Spanish

### Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com  
Languages spoken include: Spanish, English

### Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com  
Languages spoken include: Portuguese, English

## DNP 3.0 Master

The DNP 3.0 Master driver provides extensive support for Master implementations of the protocol. The serial port on the gateway is user-configurable to support the DNP 3.0 protocol (Master, Baud Rate, etc).

### General Parameters

Internal Database	Binary Inputs: 0 to 500 word count Analog Inputs: 0 to 500 points Counters: 0 to 250 points Binary Outputs: 0 to 500 word count Analog Outputs: 0 to 500 points
DNP Mode	DNP 3.0 Master – Level 2
DNP Object Support	DNPM Driver Manual contains full Object Definition documentation

### DNP Master

Node address	0 to 65534 – software selectable
Slave count	Up to 40 slave devices
Command count	Up to 300 user defined commands to interface with remote slave devices

## General Specifications

The ProLinx Communication Modules provide connectivity for two or more dissimilar network types. The modules, encased in sturdy extruded aluminum, are stand-alone DIN-rail mounted protocol gateways, providing communication between many of the most widely used protocols in industrial automation today.

## Hardware Specifications

Specification	Description
Power Supply	24 VDC nominal 18 to 36 VDC allowed Positive, Negative, GND Terminals 2.5 mm screwdriver blade
Current Load	500 mA max@ 24 VDC
Operating Temperature	-20 to 50°C (-4 to 122°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Relative Humidity	5 to 95% (non-condensing)
Dimensions	Standard: 5.20H x 2.07W x 4.52D in. (13.2cmH x 5.25cmW x 11.48cmD) Extended: 5.20H x 2.73W x 4.52D in. (13.2cmH x 6.934cmW x 11.48cmD)
LED Indicators	Power and Module Status Application Status Serial Port Activity LED Serial Activity and Error LED Status
Configuration Serial Port	DB-9M RS-232 only No hardware handshaking

Specification	Description
Ethernet Port (Ethernet modules only)	RJ45 Connector Link and Activity LED indicators
Application Serial Ports	RS-232/422/485 RS-232 handshaking configurable RS-422/485 screw termination included
Serial Port Isolation	2500V RMS port signal isolation per UL 1577 3000V DC min. port to ground and port to logic power isolation
Shipped with Each Unit	Mini-DIN to DB-9M serial cables 4 ft RS-232 configuration cable 2.5mm screwdriver CD (docs and Configuration utility) RS-422/485 DB-9 to Screw Terminal Adaptor (1 or 4, depending on ports)

## ProSoft Configuration Builder

ProSoft Configuration Builder (PCB) provides a quick and easy way to manage module configuration files customized to meet your application needs. PCB is not only a powerful solution for new configuration files, but also allows you to import information from previously installed (known working) configurations to new projects.

## Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

## Ordering Information

To order this product, please use the following:

**5201-MNET-DNPM** Modbus TCP/IP to  
DNP 3.0 Master Gateway

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

### Distributors:

Place your order by email or fax to:

**North American / Latin American / Asia Pacific**  
orders@prosoft-technology.com,  
fax to +1 661.716.5101

### Europe

europe@prosoft-technology.com,  
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.  
May 03, 2007