



DH-485 to PROFIBUS DP Master Gateway 5104-DH485-PDPM

The DH485-PDPM modules are the ideal solution for the many applications where DH-485 connectivity can be used to integrate a PROFIBUS DP slave device into a system. The DH-485 gateway is a powerful module designed with both Master and Slave support, enabling easy connection to Rockwell Automation PLCs (CLX, SLC, PLC, CPLX, and similar devices). In combination with the PROFIBUS DP Master device support, the module provides a very powerful interface to the many PROFIBUS slave devices which are in use in the industrial marketplace today. Applications for the module are found in most industries, especially Manufacturing, Oil and Gas, Electrical Power and Food Processing.

How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English

DISCONTINUED

DH-485 to PROFIBUS DP Master Gateway

5104-DH485-PDPM

The ProLinx DH-485 to PROFIBUS DP Master Gateway creates a powerful connection between devices on a DH-485 network and a PROFIBUS slave device. This stand-alone DIN-rail mounted protocol gateway provides one DH-485 configurable serial port and PROFIBUS DP Master port.

The DH-485 protocol driver supports the Master and the Slave modes of the protocol on each port, providing powerful data transfer capability with Rockwell Automation PLCs and HMIs. All DH-485 ports are individually configurable. User configurable data mapping make the interface an easy to use and powerful data transfer tool.

The PROFIBUS DP Master protocol driver supports Master implementations of the protocol on either a Mono-Master or Multi-Master network.

DH-485

The DH-485 protocol in its native form is a peer to peer token passing network. The ProLinx DH-485 driver accesses the network functioning either as a Master or as a Slave.

General Protocol Information

Error Checking	BCC and CRC
Communication Parameters	Local Station ID: 0 to 31 Port 0 Baud Rate: 110 to 38.4K baud Port 1 Baud Rate: 110 to 19200 baud Stop Bits: 1 or 2 Data Size: 7 or 8 bits Parity: None, Even, Odd RTS Timing delays: 0 to 65535 ms

DH-485 Slave Mode

In Slave mode, the module accepts commands from one or more Masters to read/write data stored in the module's internal data memory. In this mode, the ProLinx unit is answering DH-485 commands and has the appearance of an SLC processor to the network.

DH-485 Master Mode

In Master mode, the ProLinx DH-485 driver will actively gather data from other devices on the network, controlling the read/write data transfer between the gateway and other DH-485 devices, such as SLC processors. Data transfer can be initiated and executed

with the other devices without any ladder logic being required in the Rockwell Automation slave hardware.

DH485 Functioning as a Master

Command List	Up to 100 command per master port, each fully configurable for function, slave address, register to/from addressing and word/bit count
Polling of command list	User configurable polling of commands, including disabled, continuous and on change of data (write only)

PROFIBUS DP Master

The PROFIBUS Master protocol driver exists as a single port implementation. The driver can be configured as a Class 1 PROFIBUS Master to continuously interface with other PROFIBUS slave devices. The unit is also used for configuration of the nodes on the PROFIBUS network. It provides access to both standard as well as extended diagnostic information.

General Parameters

Communication parameters	Baud Rate: 9.6 kbit/s – 12 Mbit/s
--------------------------	-----------------------------------

PROFIBUS Master

Command List	Read Diag Global Cmd Read Cntrs Reset Cntrs
Node address	0 - 125 – software selectable.
Status Data	Error codes, counters and port status available per configured slave on the network.

General Specifications

The ProLinx Communication Modules provide connectivity for two or more dissimilar network types. The modules, encased in sturdy extruded aluminum, are stand-alone DIN-rail mounted protocol gateways, providing communication between many of the most widely used protocols in industrial automation today.

Hardware Specifications

Specification	Description
Power Supply	24 VDC nominal 18 to 36 VDC allowed Positive, Negative, GND Terminals 2.5 mm screwdriver blade
Current Load	500 mA max@ 24 VDC
Operating Temperature	-20 to 50°C (-4 to 122°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Relative Humidity	5 to 95% (non-condensing)
Dimensions	Standard: 5.20H x 2.07W x 4.52D in. (13.2cmH x 5.25cmW x 11.48cmD) Extended: 5.20H x 2.73W x 4.52D in. (13.2cmH x 6.934cmW x 11.48cmD)

Specification	Description
LED Indicators	Power and Module Status Application Status Serial Port Activity LED Serial Activity and Error LED Status
Configuration Serial Port	DB-9M RS-232 only No hardware handshaking
Ethernet Port (Ethernet modules only)	RJ45 Connector Link and Activity LED indicators
Application Serial Ports	RS-232/422/485 RS-232 handshaking configurable RS-422/485 screw termination included
Serial Port Isolation	2500V RMS port signal isolation per UL 1577 3000V DC min. port to ground and port to logic power isolation
Shipped with Each Unit	Mini-DIN to DB-9M serial cables 4 ft RS-232 configuration cable 2.5mm screwdriver CD (docs and Configuration utility) RS-422/485 DB-9 to Screw Terminal Adaptor (1 or 4, depending on ports)

ProSoft Configuration Builder

ProSoft Configuration Builder (PCB) provides a quick and easy way to manage module configuration files customized to meet your application needs. PCB is not only a powerful solution for new configuration files, but also allows you to import information from previously installed (known working) configurations to new projects.

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.