

Universal QuickServer Gateway PS-QS-2010-F (250 Point) PS-QS-2210-F (500 Point)

The QuickServer line of communication gateways are designed to link building automation driven networks with industrial control networks. The QuickServer gateways are available with limits of up to 250 or 500 points of application data.

Custom configuration services are also available for the QuickServer gateways. The user will be asked to fill out a worksheet, and answer some basic questions pertaining to the application, and a custom configuration will be provided along with the unit, reducing time to commission.



Features

- ◆ Ability to interface up to 250 or 500 points of common BAS protocols depending on gateway
 - EtherNet/IP™ to BACnet™ MS/TP or BACnet/IP
 - Modbus® RTU or TCP/IP to BACnet MS/TP or BACnet/IP
 - ◆ Multi-configuration capability; specific configurations selectable via software
 - ◆ DIN rail mount included with gateway
-

Specifications

Field Connections

Specification	Description
Ethernet	10/100 RJ45
Serial Ports (2)	(1) RS-485/RS-232 (1) RS-485

Environment

Specification	Description
Operating Temperature	-20°C to 70°C (-4°F to 158°F)
Relative Humidity	10% to 95% RH, with no condensation

Power Requirements

Specification	Description
Power	9 to 30 VDC or VAC
Current Draw	250 mA @12 V

Agency Approvals & Certifications

Please visit our website: www.prosoft-technology.com



Where Automation
Connects™

Ordering Information

To order this product, please use the following:

Universal QuickServer Gateway

PS-QS-2010-F (250 Point)

PS-QS-2210-F (500 Point)

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to:

www.prosoft-technology.com

and select *Where to Buy* from the menu.

Copyright © 2020 ProSoft Technology, Inc.
All Rights Reserved. 9/2/2020

Specifications subject to change without notice.