



DF1 Half/Full Duplex Master/ Slave Communication Module for Remote Chassis MVI56-DFCMR

The MVI56 DF1 Master/Slave Communication Module with Reduced Data Block is a ControlLogix backplane compatible module that allows Rockwell Automation ControlLogix I/O compatible processors to easily interface with DF1 protocol compatible devices and hosts. Devices commonly supporting the protocol include Rockwell Automation PLCs and power monitoring equipment, as well as several other third party devices in the marketplace.

This module uses a small I/O data area for data transfer between the module and the ControlLogix processor, making it ideal for ControlNet or Ethernet applications with the module in a remote rack.

Features and Benefits

The MVI56-DFCMR (DF1 Communication Module with Remote Chassis) allows Rockwell Automation ControlLogix I/O compatible processors to interface easily with other DF1 protocol compatible devices. Compatible devices include not only Modicon PLCs (which all support the DF1 protocol) but also a wide assortment of end devices.

The module has two serial ports supporting the DF1 protocol, with each port user-configurable to act as a master or as a slave. Data transfer between the module and the ControlLogix processor is asynchronous to the DF1 network, with the module's internal database being used to exchange data between the processor and the DF1 network.

General Specifications

- Single Slot – 1756 backplane compatible
- Local or remote rack
- The module is recognized as an Input/Output module and has access to processor memory for data transfer between processor and module
- Ladder Logic is used for data transfer between module and processor.
- Configuration data obtained through user-defined ladder. Sample ladder file included

Hardware Specifications

Specification	Description
Backplane Current Load	800 mA @ 5 V
Operating Temperature	0 to 60°C (32 to 140°F)

DF1 Half/Full Duplex Master/Slave Communication Module for Remote Chassis MVI56-DFCMR

The MVI56-DFCMR module is the ideal solution for many applications where DF1 protocol connectivity must be added to a ControlLogix platform. The MVI56-DFCMR module can be found in many industrial sectors and in the following applications:

- Foreign device data concentrator
- SCADA System Pipelines and offshore platforms
- Food processing
- Mining
- Pulp and paper

How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+60.3.7941.2888, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe - Middle East - Africa

+33.(0)5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, info@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America

+52.222.264.1814, support.la@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55.11.5084.5178, brasil@prosoft-technology.com
Languages spoken include: Portuguese, English

Specification	Description
Storage Temperature	-40 to 85°C (-40 to 185°F)
Shock:	30g Operational 50g non-operational Vibration: 5 g from 10 to 150 Hz
Relative Humidity	5 to 95% (non-condensing)
LED Indicators:	Module Status Backplane Transfer Status Application Status Serial Activity
Debug/Configuration port (CFG)	
CFG Port (CFG)	RJ45 (DB-9M with supplied cable) RS-232 only
Application ports (PRT1 & PRT2)	
Full hardware handshaking control, providing radio, modem and Multi-drop support	
Software configurable communication parameters	Baud rate: 110 to 115,200 baud, depending on protocol RS-232, 485 and 422 Parity: none, odd or even Data bits: 5, 6, 7, or 8 Stop bits: 1 or 2 RTS on/off delay: 0 to 65535 ms
App Ports (P1,P2) (Serial modules)	RJ45 (DB-9M with supplied cable) RS-232 handshaking configurable 500V Optical isolation from backplane
Shipped with Unit	RJ45 to DB-9M cables for each port 6-foot RS-232 configuration cable

Functional Specifications

This module uses a small I/O data area for data transfer between the module and the ControlLogix processor.

DF1 ports

- Full and half duplex modes supported
- CRC and BCC error checking
- Full hardware handshaking control provides radio, modem and Multi-drop support
- Memory usage is completely user configurable, supporting the storage and transfer of up to 5000 registers to/from the control processor
- Up to 125 word read and write command lengths supported
- Floating point data movement supported

DF1 Master Protocol Specifications

The ports on the DF1 module can be individually configured as Master ports. When configured in master mode, the DFCM module is capable of reading and writing data to remote DF1 devices, enabling the processor to act as a SCADA sub-master.

- Command List: Up to 100 commands per Master port, each fully-configurable for function, slave address, register to/from addressing and word/byte count

- Status Data: Error codes available on an individual command basis. In addition, a slave status list is maintained per active master port.
- Polling of Command List: User-configurable polling of commands, including disabled, continuous, and on change of data (write only)

DF1 Slave Protocol Specifications

The module accepts DF1 commands from an attached DF1 master unit. When in slave mode, the module can accept DF1 commands from a master to read/write data stored in the module's internal registers. This data can be derived from other DF1 slave devices on the network through a master port or from the processor and is easily transferred to the processor's data registers.

Tested Hardware Connections

Several hardware connections have been tested by ProSoft Technology or have been customer field tested. To our knowledge, the following physical connections have been successful:

- RA Panel view (Full Duplex point-point, DFCM as slave)
- RA Processors (Full/Half duplex, DFCM as either master or slave)
- RA Power Monitors (485 Half-Duplex DFCM as Master)

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

To order this product, please use the following:

MVI56-DFCMR DF1 Half/Full Duplex Master/Slave Communication Module for Remote Chassis

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

Copyright © ProSoft Technology, Inc. 2019. All Rights Reserved.
May 3, 2019